

DuroMaxx steel reinforced polyethylene pipe from Contech Engineered Solutions provides an effective and economical solution that is renowned for its strength and durability even in the tightest of spaces.

- Longer Lengths
- Lighter Weights
- Efficient Trench
- Installation Savings



Product Comparison

DuroMaxx Steel Reinforced Polyethylene Pipe (SRPE) vs. RCP

| Nominal Diameters | Outside Diameters (OD) | | | Trench Width | | | Handling Weights | | | Profile Height vs. Wall Thickness | | | | |
|-------------------|------------------------|------------|------------|--------------|------------|------------|------------------|------------|------------|-----------------------------------|----------------------|------------------------------------|----------------------|------------------------------------|
| | SRPE | RCP Wall B | RCP Wall C | SRPE | RCP Wall B | RCP Wall C | SRPE | RCP Wall B | RCP Wall C | Vertical Headroom Advantages | | | | |
| | | | | | | | | | | SRPE Wall Profile Height | RCP Wall B Thickness | SRPE Headroom Advantage vs. Wall B | RCP Wall C Thickness | SRPE Headroom Advantage vs. Wall C |
| (in) | (in) | (in) | (in) | (in) | (in) | (in) | (lbs/lf) | (lbs/lf) | (lbs/lf) | (in) | (in) | (in) | (in) | (in) |
| 30 | 30.9 | 37 | 38.5 | 50.6 | 58.3 | 60.1 | 18.8 | 410 | 500 | 0.7 | 3.5 | 3.3 | 4.25 | 4.1 |
| 36 | 37.1 | 44 | 45.5 | 58.4 | 67.0 | 68.9 | 23.6 | 563 | 670 | 0.85 | 4 | 3.8 | 4.75 | 4.5 |
| 42 | 43.2 | 51 | 52.5 | 66.0 | 75.8 | 77.6 | 27 | 745 | 860 | 0.95 | 4.5 | 4.3 | 5.25 | 5.0 |
| 48 | 49.5 | 58 | 59.5 | 73.5 | 84.5 | 86.4 | 30.8 | 920 | 1055 | 1.2 | 5 | 5.0 | 5.75 | 5.8 |
| 54 | 55.5 | 65 | 66.5 | 81.4 | 93.3 | 95.1 | 36.1 | 1125 | 1270 | 1.2 | 5.5 | 5.2 | 6.25 | 6.0 |
| 60 | 61.4 | 72 | 73.5 | 88.8 | 102.0 | 103.9 | 42.9 | 1340 | 1505 | 1.2 | 6 | 5.8 | 6.75 | 6.6 |
| 66 | 67.8 | 79 | 80.5 | 96.8 | 110.8 | 112.6 | 56.9 | 1580 | 1755 | 1.4 | 6.5 | 6.1 | 7.25 | 6.9 |
| 72 | 73.7 | 86 | 87.5 | 104.1 | 119.5 | 121.4 | 65.6 | 1840 | 2030 | 1.4 | 7 | 6.7 | 7.75 | 7.5 |
| 84 | 85.9 | 100 | 101.5 | 119.4 | 137.0 | 138.9 | 76.3 | 2410 | 2655 | 1.6 | 8 | 7.7 | 8.75 | 8.4 |
| 96 | 97.8 | 114 | 115.5 | 134.3 | 154.5 | 156.4 | 87 | 3095 | 3355 | 1.65 | 9 | 8.9 | 9.75 | 9.6 |
| 108 | 111.3 | 128 | 129.5 | 151.1 | 170.7 | 172.7 | 100 | 3860 | 4180 | 1.65 | 10 | 8.4 | 10.75 | 9.1 |
| 120 | 121.9 | 142 | 143.5 | 164.4 | 189.5 | 191.4 | 109 | 4716 | 5066 | 1.65 | 11 | 10.8 | 11.75 | 11.5 |

For more information, call 800.338.1122 or visit our web site: www.ContechES.com

NOTHING IN THIS CATALOG SHOULD BE CONSTRUED AS AN EXPRESSED WARRANTY OR AN IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. SEE THE CONTECH STANDARD CONDITIONS OF SALE (VIEWABLE AT WWW.CONTECHES.COM/COS) FOR MORE INFORMATION.

DuroMaxx is supported by Plastream technology.

